

CLAIMS

1 1. A hand power tool, comprising a housing; at least one
2 handle having at least one gripping part; at least one elastic, vibration-
3 damping element; a mounting part mounted on said elastic element; a said
4 gripping part being mounted on said housing through said elastic element
5 and through said mounting element; and at least one movable safety
6 element through which said gripping part is connected with said mounting
7 part.

1 2. A hand power tool as defined in claim 1, wherein said safety
2 element is formed as a bendable part.

1 3. A hand power tool as defined in claim 2, wherein said safety
2 element is formed as a rope.

1 4. A hand power tool as defined in claim 1, wherein said safety
2 element is formed as a rigid component which is connected through said
3 elastic element with said gripping part and said mounting part.

1 5. A hand power tool as defined in claim 1, wherein said elastic
2 element surrounds said safety element.

1 6. A hand power tool as defined in claim 4, wherein said safety
2 element is arranged in said elastic element along a central axis.

1 7. A hand power tool as defined in claim 1, wherein said safety
2 element in a mounted condition is loaded by pulling, and said elastic element
3 in a mounted condition is loaded by pressure.

1 8. A hand power tool as defined in claim 1, wherein said safety
2 element is formed as a band which surrounds said elastic element.

1 9. A hand power tool as defined in claim 1, wherein said safety
2 element determines a maximum deviation of said elastic element from a
3 base position in a direction selected from the group consisting of a tilting
4 direction, a displacing direction, and both.